Go Go Ultra Lite, 1000T – Specifications

PARAMETER	1000T
LENGTH	51.15inch
REAR WIDTH	20.35inch
HEIGHT	37.4inch
MAX. USER WEIGHT	120 kg (264 lbs)
BATTERY CAPACITY	6.4AH*2
MAX SAFE SLOPE	8degrees at 120kg （264 lbs）
SEAT HEIGHT	20.87inch（±0.197）
MAX SPEED	6km/h
FRONT WHEEL SIZE	7.0"
REAR WHEEL SIZE	8.0"
CHARGER	DC24V2A AC100-240V
MOTOR	180W
DRIVING RANGE	12-15KM
TOTAL WEIGHT WITHOUT BATTERY	13.7 KG（30.2lbs）
BATTERY WEIGHT	1KG*2（2.2lbs*2）
GROUND CLEARANCE	0.787inch
CONTROLLER	24V/30A; Chinese Brand
VOLTAGE	24VDC（2 units）
VOLTAGE TYPE	D.C.24V
SEAT DEPTH	14.96inch
FOLDED LENGTH	17.52inch
FOLDED WIDTH	20.67inch
FOLDED HEIGHT	27.17inch
MINI TURNING RADIUS	51.18inch

The mobility scooter complies with the following standards:

a) Static, impact and strength requirements and test methods (ISO 7176-8)

b) Power and control systems for electric mobility scooters - Requirements and test methods (ISO 7176-14)

c) Testing of mobility scooters for weathering according to ISO7176-9

d) Anti-ignition requirements according to ISO7176-16